



Maintenance Platform Operating Instructions

PLEASE READ THE FOLLOWING MANUFACTURERS GUIDELINES AND RECOMMENDATIONS:-

The machine should be fitted with a crowd/rotational lock out device before the attachment is fitted and used. Should this not be fitted, please contact your dealer for advice.

To attach your platform – Tine Fixing

1. Set pallet tines to correct spacing and lock to avoid sideward movement
2. Drive fully into sockets provided on platform
3. Insert locking pin behind pallet tines (to prevent forward attachment) and secure with lynch pin

DO NOT STAND UNDER RAISED ATTACHMENT

To attach to your platform – Bracket Fixing

1. Hook up materials handler to attachment fully crowded back
2. Extend locking pins either manually or hydraulically to ensure attachment to materials handler. Visually check they are in the correct position.

DO NOT STAND UNDER RAISED ATTACHMENT



Director: G.F. Cherry

Cherry Products Ltd. Oathill, Enstone, Chipping Norton, Oxon
OX7 4ED

Tel: 01608 678 197 **Fax:** 01608 677 778

Web: www.cherryproducts.co.uk

Registered In England. 3458481 **VAT No.** 348 8353 21



Maintenance Platform Operating Instructions

Recommendations for Safe Operation

1. Always have forklift manned at all times
2. Load platform with minimum of tools and equipment required and keep tidy
3. Larger equipment should be attached to platform rails by safety chains
4. Do not drive with platform raised or use on soft or uneven/sloping ground
5. Position as close as possible to work projects
6. Always stand on platform base – do not attempt to gain extra height by climbing on safety rails
7. Keep area below platform clear of people. (The platform is fitted with kicker boards and weldmesh to avoid accidental discharge of tools and equipment but there is still a danger of falling objects)
8. Keep platform level
9. Do not use your maintenance platform for any other purpose than it was intended to be used for
10. Do not attach weights
11. Maximum operating height; 6m

DO NOT STAND UNDER RAISED ATTACHMENT

PLEASE REFER TO HSE PM28 GUIDELINES FOR FULL DETAILS

<http://www.hse.gov.uk/pubns/pm28.htm>



Director: G.F. Cherry

**Cherry Products Ltd. Oathill, Enstone, Chipping Norton, Oxon
OX7 4ED**

Tel: 01608 678 197 Fax: 01608 677 778

Web: www.cherryproducts.co.uk

Registered In England. 3458481 VAT No. 348 8353 21